

DIGIMIC®

Digital Interpreter Console DDol



Description

The tried and tested operating concept of the interpreter console from the high-end CDSVAN series, developed in cooperation with interpreters, also features in the DIGIMIC DDol.

It's clearly arranged controls, its large, bright display and the illuminated buttons allow straight and intuitive operation. Up to 3 selectable output channels and 5 preselectable monitoring languages are just as self-understood as separate speech channels providing a link to technical team or the chairperson.

All common (mono and stereo) headphones can easily be connected to the console and in combination with various microphone types or combined headsets it guarantees maximum comfort for the interpreter. The interpreter console is divided into 3 sections:

Speaking section

- Three outgoing channels (A/B/C)
- Microphone ON/ OFF button
- Mute button to mute the activate microphone temporarily
- Clear indication of active and occupied channels

Listening and relay section

- 5 preselectable relay channels
- separate floor button
- Relay interpretation quality indicator

Monitoring section

- Loudspeaker with channel selector to monitor all languages
- All loudspeakers within one both will be muted automatically, when a DDOL in the booth goes live

Additional features

- Operator and/ or chairman call
- Auto Relay feature
- Various take-over modes programmable
- "Hearing guard" LED to indicate headphone volume level

Technical Data

Complies with the standards IEC914 and IEC2603.2

- Sample rate 48kHz
- Resolution 24 BIT
- Frequency response: 20 - 20,000 Hz
- OR + 7 channels
- Latency end to end 1.5 ms
- LC-Display, 2 x 56 characters, backlit

Connections

- PREVIOUS (D9) for interconnection
- NEXT (D9) for interconnection
- Microphone TM58/6 or TMD01 (Minicon socket) lockable
- Headphones (3.5/6.3 mm jack)
- Electret Headset 8-pin socket (DIN)

Housing

- Lower part: robust plastic, grey
- Operation panel: aluminium, "silver" anodized
- WxHxD: (305 x 96 x 175) mm
- Weight: 1.5 kg

Accessories (not included in delivery)

- **TM58/6** Conference Microphone (01.0560)
- **TM58/6-500** Conference Microphone 500mm (01.0561)
- **TM58/6-2S** Conference Microphone with 2 goosenecks (01.0560.S2)
- **TMD/01** Conference Microphone with integrated windshield functionality (01.0701)
- **K45/6** Dynamic Headphone (03.0270), also with 1.5m cable (K45/16 - 03.0290)
- **PMX60** Dynamic Conference Headphone with neckband (03.5501)
- **HS394** Lightweight Interpreter Headset (03.5530)
- **HS460** Interpreter Headset (03.5550)

BRÄHLER ICS is committed to continually improving its products and so reserves the right to make technical modifications without notice.

WPF05 0700.E:120906